



AquaRite® Pro Touch

AN EVOLUTION OF SALT CHLORINATOR ACCORDING OUR TIME

- **Salt chlorinator combined with water treatment controls**
- Available also in **low salinity**
- Touch screen included
- **From 3,2 gr salt/L for standard salinity and from 1,2 gr salt/L for low salinity**
- **Transparent cell** with Hayward® T-Cell technology
- **Automatic and continuous pH and rX control**
- **Probe holder including prefilter of 65 microns.**

INCLUDED



TOUCH SCREEN INCLUDED

For easy and intuitive use



Transparent cell with Hayward® T-Cell technology



Double probe holder



Peristaltic pump



pH - ORP and Goldline probes

AQUARITE® PRO TOUCH

| Description | AQR-PROT-T3 | AQR-PROT-T9 | AQR-PROT-T15 | AQR-PROT-T3LS |
|-------------------------|---|-------------|--------------|---------------|
| Chlorine production | 10 g/h | 20 g/h | 30 g/h | Equiv 10 g/h |
| Pool size up to | 60 m³ | 95 m³ | 150 m³ | 50 m³ |
| Salt concentration | From 3,2 g/L | | | From 1,2 g/L |
| Display | Touch screen (4,3") removable screen for remote installation | | | |
| pH control | Included with variable pH pump (1,5L/h - 7L/h) | | | |
| rX control | Included (rX gold sensor) | | | |
| Temperature | Included in the cell | | | |
| Superchloration mode | Included (24 hours) | | | |
| Manual adjustment of Cl | Configurable by gramage | | | |
| Cover detection | Configurable production level 0-100% depending on open or closed pool cover | | | |
| Flow switch | Mechanical with 3/4" connection | | | |
| Self cleaning | Reverse polarity every 360 min | | | |
| Protection | Flow switch | | | |
| Alarms | AL3 for pH injection / AL4 for cell configurable | | | |
| Control box dimensions | 270 x 220 x 120 | | | |

AVAILABLE OPTIONS

| Description | AQR-PROT-T3 | AQR-PROT-T9 | AQR-PROT-T15 | AQR-PROT-T3LS |
|----------------------|---------------|-------------|--------------|---------------|
| Cleaning base | GLX-CELLSTAND | | | |
| External temperature | T-OPTION-TEMP | | | |
| Pool Terre | KV02 | | | |